



Belaire Range of Mobile Air-Conditioners

H2800

Introduction:

With outstanding performance and only 85 cm in length, the Houghton Belaire H2800 provides greater flexibility for hatches, solar panels, satellite dishes and other equipment without sacrificing year-round comfort.

Features:

- The H2800 is a low profile, compact, light, and powerful unit :
 - Its small roof top foot print (855 L x 657mm W) allows for better fit with other roof top accessories such as solar panels and hatches.
 - Low profile height of 215mm - allows entry under low car ports.
- 4-way outlet from the interior unit allows air flow to be directed throughout the living space.
- Reverse cycle heat pump delivers effective heating and cooling performance from -5°C to +50°C.
- Strong, lightweight, and durable chassis and canopy made from UV stabilised polypropylene. Able to withstand the toughest conditions and will never rust.
- Remote control allows access to all air conditioner functions from the comfort of your dining area, chair or bed.
- Easy to read LED display shows mode and setting temperatures. Display can be turned on or off via the remote control.
- 3 fan speeds and 5 operation modes - Cool, Heat, Dry (dehumidify), Fan and Auto gives you ultimate control over your living environment.
- Advanced micro controller automatically takes care of compressor protection, fault monitoring & coil defrost. Timer function allows you to program start and stop times. Great for turning on unit to pre-cool the RV before your return or turning unit off each night if you forget.



Specification:

Power supply	1PH/230~240V/50Hz	Maximum input power	1430W
Cooling capacity	2800W	Maximum current	6.3 A
Power input cooling	1150W	Weight of outdoor unit	32.5 kg
Current cooling	5.0 A	Weight of plenum	3 kg
Heating capacity	2600W	Installation opening (mm)	360 × 360. Optional adapter required for 400 × 400
Power input heating	1120W	Outdoor unit dimension (mm)	855L × 657W × 215H
Current heating	4.8 A	Plenum dimension (mm)	575L x 556W × 49H